



Acier d'armature Reinforcing bars

Dimensions Pouce/Inch	Dimensions MM	LB./PI. LIN LB./LIN.FT
3	---	0,376
4	---	0,668
5	---	1,043
6	---	1,502
7	---	2,045
8	---	2,670
---	10	0,527
---	15	1,056
---	20	1,582
---	25	2,637
---	30	3,693
---	35	5,276
---	45	7,912
---	55	13,188

Nuance / Grade	40	275,44 Mpa
Nuance / Grade	50	344,30 Mpa
Nuance / Grade	60	413,16 Mpa
Nuance / Grade	300	43 567 lb/po²
Nuance / Grade	350	50 828 lb/po²
Nuance / Grade	400	58 089 lb/po²

Treillis métallique Wire mesh

Dimensions Pouce/Inch	Dimensions MM	LB./100 PI CAR LB./100 SQ. FT
4 x 4 x 9/9S	102 x 102 MW11,1xMW11,1	37
x 8/8	MW13,3xMW13,3	44
x 6/6S	MW18,7xMW18,7	62
x 4/4S	MW25,8xMW25,8	85
6 x 6 x 10/10S	152 x 152 MW9,1xMW9,1	21
x 9/9S	MW11,1xMW11,1	25
x 8/8S	MW13,3xMW13,3	30
x 6/6S	MW18,7xMW18,7	42
x 4/4S	MW25,8xMW25,8	58
x 2/2	MW34,9xMW34,9	78
x 0/0	MW47,6xMW47,6	107
12 x 12 W3,4/W3,4S	305 x 305 MW22,2xMW22,2	25
W5,8/W5,8S	MW51,6xMW51,6	42